

Accessories:

Type	Description	Dimensions L x W mm (in)	Type of Drive Petrol Engine kW	Electric Voltage / AC (50 Hz) V	Dead Weight kg (lbs)	Working Load Limit/WLL -200 mbar kg (lbs)	Order-Number
QJ-ESP-320-59/ 59	Suction Plate	590 x 590 (23.23 x 23.23)			13 (29)	320 (705)	42420102
QJ-ESP-400-98/ 48	Suction Plate	980 x 480 (38.58 x 18.90)			19 (42)	400 (882)	42420104
QJ-ESP-600- 78,5/78,5	Suction Plate	785 x 785 (30.91 x 30.91)			22 (49)	600 (1,323)	42420106
QJ-ESP-350- 151/29	Suction Plate	1,510 x 290 (59.45 x 11.42)			18 (40)	350 (772)	42420108
QJ-ESP-170-90/ 25	Suction Plate	900 x 250 (35.43 x 9.84)			13 (29)	170 (375)	42420110
QJ-ESP-250-90/ 35	Suction Plate	900 x 350 (35.43 x 13.78)			14 (31)	250 (551)	42420112
QJ-ESP-500- 140/40	Suction Plate	1,400 x 400 (55.12 x 15¾)			21 (46)	500 (1,102)	42420114
SE-H Generator Honda EU 22 i	230 V 50 Hz petrol engine		2.25	230	22.5 (50)		52500243
Adapter QJ	For Rotator				1.5 (3.31)		40110319
Adapter QJ for SPEEDY angeled suction plates	Adapter for mounting SPEEDY angeled suction plates to QUICKJET QJ				6.1 (13)		42420118

011223 Technical data contained in this catalogue can be modified without prior notice in the interest of progress. Illustrations are exemplary and non-binding. No liability accepted for any misprints, mistakes and errors. * Details in the general sales conditions at the end of the catalogue or at www.probst-handling.com/en/gtc



Wheelset QJ-RS for QUICKJET QJ-600-E



With its wheelset QJ-RS the QUICKJET becomes the perfect, mobile vacuum generator for economic and accurate installation of natural stones, concrete slabs, large-size pavers etc.

Furthermore the wheelset protects the suction plate during storage and transport. The wheelset consists of a base plate with integrated wheels. The QUICKJET QJ and suction plate are just fixed by means of quick release fasteners.

- Durable surface protection by galvanizing.

QJ-RS

Type	Description	Dead Weight kg (lbs)	Order-Number
QJ-RS	Wheelset for QUICKJET	18 (40)	42420083