



SRG-UNI-1,5



SRG-1,5

Manhole and Cone Chain Clamp SRG

For transporting manhole rings and cones.

SRG-1,5, SRG-3 and SRG-3-L suitable for manhole rings as per DIN 4034 part 2.

With Lifting Strap: SRG-UNI-1,5, SRG-UNI-3.

With High-tensile Lifting Chain: SRG-UNI-1,5-K, SRG-UNI-3-K, SRG-1,5, SRG-3, SRG-3-L.

- Manhole and Cone Chain Clamp SRG-UNI: especially easy handling and light-weight. Automatically adjustable clamping range of the claws to the thickness of the pipe walls.

SRG-UNI-1,5: for manhole rings as per DIN 4034, part 2 and cones.

SRG-UNI-3: for manhole rings as per DIN 4034, part 1 + 2 and cones.

Type	Dimensions L x W x H mm (in)	Number of Claws Pcs.	Diameter Nominal Diameter mm (in)	Dead Weight kg (lbs)	Gripping Range mm (in)	Working Load Limit/ WLL kg (lbs)	Order-Number
SRG-UNI-1,5	360 x 330 x 380 (14.17 x 12.99 x 14.96)	3	800 – 2,000 (31.49 – 78.74)	28 (62)	40 – 120 (1.57 – 4.72)	1,500 (3,307)	54400015
SRG-UNI-1,5-K	360 x 330 x 380 (14.17 x 12.99 x 14.96)	3	800 – 2,000 (31.49 – 78.74)	32 (71)	40 – 120 (1.57 – 4.72)	1,500 (3,307)	54400018
SRG-UNI-3	460 x 410 x 430 (18.11 x 16.14 x 16.93)	3	800 – 2,000 (31.49 – 78.74)	40 (88)	60 – 180 (2.36 – 7.09)	3,000 (6,614)	54400014
SRG-UNI-3-K	460 x 410 x 430 (18.11 x 16.14 x 16.93)	3	800 – 2,000 (31.49 – 78.74)	45 (99)	60 – 180 (2.36 – 7.09)	3,000 (6,614)	54400019
SRG-1,5	390 x 330 x 220 (15.35 x 12.99 x 8.66)	3	400 – 2,000 (15.74 – 78.74)	31 (68)	40 – 120 (1.57 – 4.72)	1,500 (3,307)	54400001
SRG-3	460 x 400 x 250 (18.11 x 15.74 x 9.84)	3	400 – 2,000 (15.74 – 78.74)	55 (121)	50 – 180 (1.97 – 7.09)	3,000 (6,614)	54400002
SRG-3-L	460 x 400 x 250 (18.11 x 15.74 x 9.84)	3	400 – 3,000 (15.74 – 118.11)	58 (128)	50 – 180 (1.97 – 7.09)	3,000 (6,614)	54400003