_probst



SVZ-UNI



Manhole and Cone Installation Clamp SVZ-UNI



This universal manhole and cone clamp SVZ-UNI enormously rationalizes transport and installation of manhole elements.

Especially suitable for manhole bases, rings (height 500 mm/ $19^{3/4}$ inch or larger) and cones with inner diameters of:

SVZ-UNI: 625/700/800/1.000/1.050/1.200/1.250/1.350/1.500 mm. (24.60/27.55/31.49/39.37/41.33/47.24/49.21/53.14/59 inch).

ŠVZ-UŃI-UK: (725/800/900/1.000/1.050/1.200/1.250/1.350/1.500 mm. (28.54/31.49/35.43/39.37/41.33/47.24/49.21/53.14/59 inch).

- With additional suspension position for a more horizontal hanging of the cones.
- An additional operator is not necessary as the driver of the lifting machine "switches" the SVZ-UNI from gripping to releasing by a slight movement of the lifting hook.
- The settings to the required diameters of the products is done very quickly through plug bolts. A rearrangement of the settings is not necessary when handling manhole rings and cones, as the SVZ-UNI has got two gripping levels.
- Efficient and economic handling of all kinds of manhole elements.
- High tensile chain suspension with eyelet.
- Durable surface protection by galvanizing.

Туре	Description	Diameter Nominal Diameter mm (in)	Dead Weight kg (lbs)	Working Load Limit/WLL kg (lbs)	Order - Number
SVZ-UNI	Global	625 - 1,500 (24.61 - 59.06)	103 (227)	2,500 (5,512)	54000046
SVZ-UNI-UK	Specially for UK	900 – 1,500 (35.43 – 59.06)	96 (212)	2,500 (5,512)	54000047

Accessories:

Туре	Description	Diameter Nominal Diameter mm (in)	Dead Weight kg (lbs)	Order - Number
SVZ adaptor set	Surcharge for higher nominal width	1,800 (70.87)	25 (55)	44000064
SVZ-UNI-AS	Set of Adaptors for height support, in order to also grip rings with 250 mm height.		5.4 (12)	44000079