probst



STAZ-UNI

STAZ-UNI

Fork Lift Grab STAZ-UNI

Specially designed for heavy duty work with fork lift trucks.

For gripping heavier loads, or packs produced on multi-layer production machines. In particular used in conjunction with steel finger grippers. Can also be used for gripping packs of pavers which are not vertically steel strapped.

- Light-weight, yet with a high carrying capacity due to the use of high-tensile steel for load-bearing parts.
- Can fit all the usual packs of building materials due to a large opening range and to the exchangeable grippers which come in various lengths and designs.
- I Fully hydraulic parallel opening range. Low-maintenance steel-plastic sliding guides.
- Manually adjustable pressure relief valve.
- I Oil Pressure Gauge.
- Plastic sliding guides come with a 5 year guarantee.

Туре	Inside Height mm (in)	Dead Weight kg (lbs)	Hydraulic Connection Pressure bar (psi)	Opening Width Main Gripper mm (in)	Working Load Limit/WLL kg (lbs)	Gripper Base Length Main Gripper mm (in)	Order-Number
STAZ-UNI-0700	700 (27.56)	500 (1,102)	180 - 210 (2,611 - 3,046)	370 - 1,370 (14.57 - 53.94)	4,000 (8,818)	1,250 (49.21)	57000700-1250
STAZ-UNI-0850	850 (33.46)	505 (1,113)	180 - 210 (2,611 - 3,046)	370 – 1,370 (14.57 – 53.94)	4,000 (8,818)	1,250 (49.21)	57000850-1250
STAZ-UNI-1000	1,000 (39.37)	525 (1,157)	180 - 210 (2,611 - 3,046)	370 - 1,370 (14.57 - 53.94)	3,750 (8,267)	1,250 (49.21)	57001000-1250
STAZ-UNI-1200	1,200 (47.24)	560 (1,235)	180 - 210 (2,611 - 3,046)	370 - 1,370 (14.57 - 53.94)	3,250 (7,165)	1,250 (49.21)	57001200-1250
STAZ-UNI-1300	1,300 (51.18)	575 (1,268)	180 - 210 (2,611 - 3,046)	370 - 1,370 (14.57 - 53.94)	3,000 (6,614)	1,250 (49.21)	57001300-1250
STAZ-UNI-1350	1,350 (53.15)	585 (1,290)	180 - 210 (2,611 - 3,046)	370 - 1,370 (14.57 - 53.94)	3,000 (6,614)	1,250 (49.21)	57001350-1250
STAZ-UNI-1400	1,400 (55.12)	595 (1,312)	180 - 210 (2,611 - 3,046)	370 - 1,370 (14.57 - 53.94)	2,750 (6,063)	1,250 (49.21)	57001400-1250
STAZ-UNI-1550	1,550 (61.02)	610 (1,345)	180 – 210 (2,611 – 3,046)	370 - 1,370 (14.57 - 53.94)	2,500 (5,512)	1,250 (49.21)	57001550-1250