



**NEW**

## Multiple Suction Plates MFS



MFS 7-way (rigid)



MFS 7-way (movable)

### Easy laying of up to 7 concrete blocks.

Attached to the various lifting units HE (up to HE-150), you can lay up to 7 concrete blocks safely and quickly with the Probst multiple suction plates MFS.

**MFS-150-7-S-15Rd (rigid):** Multiple suction plate (7 bellows) with various predefined hole spacings for mounting the bellows. It is also possible to lift only 5 or 6 bricks. Unused bellows can be plugged with an optionally available protective cover and sealing plate and mounted on top of the traverse for trouble-free operation.

**MFS-85-6-S-15Rd (rigid):** Multiple suction plate (6 bellows) with various predefined hole spacings for mounting the bellows. Only 4 or 5 bricks can also be lifted. Bellows that are not required can be sealed with an optionally available protective cover and sealing plate and attached to the top of the lifting beam for trouble-free operation.

**MFS-150-4-S-20Rd (rigid):** Multiple suction plate (4 bellows).

**MFS-150-7-V-15Rd (movable):** Multiple suction plate (7 bellows) with distance adjustment. DIN18318 (road construction work, paving and paving slabs) stipulates a distance between the individual stones, particularly when laying gutter stones. For this reason, a hand lever can be used to set a distance of 8 mm between the individual stones when the MFS is raised. For block length 160 mm.

**MFS-150-5-V-15Rd (movable):** Multiple suction plate (5 bellows) with adjustable spacing. DIN18318 (road construction work, paving and paving slabs) stipulates a distance between the individual stones, particularly when laying gutter stones. For this reason, a hand lever can be used on this MFS to set a distance of 8 mm between the individual stones when raised. For block length 240 mm.

- Height and angle compensation means that even rows of stones that are not completely level can be lifted.
- Fast suction process.
- Sealing bellows can be quickly replaced without tools.

Type	Dimensions oval, L x B mm (in)	Number of Suction Plates Pcs.	Dead Weight kg (lbs)	Working Load Limit/WLL -420 mbar kg (lbs)	Shifting mm (in)	Order-Number
MFS-85-6-S-15Rd	150 x 150 (5.91 x 5.91)	6	11,2 (25)	85 (187)		42101510
MFS-150-7-S-15Rd	150 x 150 (5.91 x 5.91)	7	12 (26)	150 (331)		42101500
MFS-150-4-S-20Rd	200 x 200 (7.87 x 7.87)	4	12 (26)	150 (331)		42101535
MFS-150-5-V-15Rd	150 x 150 (5.91 x 5.91)	5	14 (31)	150 (331)	8 (0.31)	42101542
MFS-150-7-V-15Rd	150 x 150 (5.91 x 5.91)	7	15 (33)	150 (331)	8 (0.31)	42101501

### Accessories:

Type	Dimensions oval, L x B mm (in)	Dead Weight kg (lbs)	Order-Number
Protective cover	150 x 150 (5.91 x 5.91)		42101506
Sealing plate	145 x 145 (5.71 x 5.71)	0.1 (0.22)	33510026