



STAZ-UNI-P

17

STAZ-UNI-KA

Fork Lift Grab STAZ-UNI-P/STAZ-UNI-KA

Specially designed for the heavy duty work with forklift truck, directly fixed to the carriage plate of the forklift.

We recommend the use of a side-shift built into the forklift. Supplied without connecting hoses to the forklift-truck.

- Light-weight, yet with a high working load limit due to the use of high-tensile steel for load bearing parts.
- Can fit all the usual packs of building materials due to a large opening range and to the exchangeable grippers which come invarious lengths and designs. Fully hydraulic parallel opening range.
- Low maintenance steel plastic sliding guides.
- Manually adjustable pressure relieve valve.
- I Oil Pressure Gauge.
- Plastic sliding guides come with a 5 year guarantee.
- Larger or modified opening widths and heights are available on request.

At **STAZ-UNI-P-1000:** grips the pack by pressing it towards the gripper close to the forklift. This achieves smallest possible load center of the pack.

At **STAZ-UNI-KA-1000:** moves both grippers synchronized towards the pack. Compact design due to integrated crane boom.

Туре	Inside Height mm (in)	Dead Weight kg (lbs)	Hydraulic Connection Pressure bar (psi)	Opening Width Main Gripper mm (in)	Working Load Limit/WLL kg (lbs)	Order-Number
STAZ-UNI-P-1000	1,000 (39.37)	440 (970)	180 - 210 (2,611 - 3,046)	580 — 1,260 (22.83 — 49.61)	2,300 (5,071)	57000087
STAZ-UNI-KA-1000	1,000 (39.37)	690 (1,521)	180 - 210 (2,611 - 3,046)	370 – 1,370 (14.57 – 53.94)	2,000 (4,409)	57000173



ASZ

Sorting Clamp ASZ

This univeral outsorting clamp has a wide adjustable opening width and can be used for a wide range of products.

There are two different variations:

- 1. ASZ for the efficient outsorting of concrete steps, kerb stones and similar.
- 2. ASZ-R for the handling of sewerage elements. The grippers are prism-shaped to grip the round contour of the rings.

Please note: Designed and suitable to grip single stones or elements only. This is not the proper equipment for handling a complete row of stones.

- Lifting eye for attaching to crane hook.
- Lifting handle.
- Handle with turning range 90° depending on space.
- Exchangeable rubber metal bars, to suit the requirements.
- Automatic release for fully automatical switch-over from "full" to "empty".